

TECHNICAL SPECIFICATIONS

DSPB-250.C DSPB-500.C DSPB-1000.C

DESCRIPTION

Double sided permanent bond tape provides a long lasting secure bond when the highest adhesion levels are required.

The tape is commonly used to replace rivets and fasteners and can be used to secure a variety of materials like glass, plastic, metal, laminates, wood and even rock of concrete for specialty applications. Applies clear for visual reference.

PRODUCT APPLICATIONS

- 0.25mm to 1.00mm works for a variety of high vibration applications
- Secures material for use in indoor and outdoor applications and harsh weather environments.
- Great permanent bond holding power

FEATURES

- Smooth, easy release from hand rolls for easy application
- Ultra strong & durable

	DSPB-250.C	DSPB-500.C	DSPB-1000.C
Peel Adhesion	20N/24mm	24N/24mm	28N/24mm
Static Shear (1000g)	1000g +10000 min	1000g +10000 min	1000g +10000 min
Shear (180 degree)	95 lbs.	105 lbs.	105 lbs.
Tape Color	Clear	Clear	Clear
Total Thickness	250 mic (0.25 mm)	500 mic (0.50 mm)	1000 mic (1.00 mm)
Adhesive	Acrylic	Acrylic	Acrylic
Application Range	35°F to 95°F	35°F to 95°F	35°F to 95°F
Operating Range	20°F to 275°F	20°F to 275°F	20°F to 275°F
Sizes (Width) Sizes	3 mm to 900 mm	3 mm to 900 mm	3 mm to 900 mm
(Length)	60 yards	60 yards	60 yards
Storage	40°F to 80°F 40% to 55% Humidity	40°F to 80°F 40% to 55% Humidity	40°F to 80°F 40% to 55% Humidity
Shelf Life	24 months	24 months	24 months
Applications	Indoor & Outdoor	Indoor & Outdoor	Indoor & Outdoor



NOMINAL VALUES

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



A Universal Company

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030

www.incrediseal.com | sales@incrediseal.com

Customer Service: (410) 825-8300