

TECHNICAL SPECIFICATIONS

DSTS-3150.C

DESCRIPTION

Double sided tissue tape provides a long lasting secure bond when the highest adhesion levels are required.

The tape is commonly used to for high temperature splicing applications in corrugated cardboard facilities. Other applications include indoor/outdoor sign backings and nameplates.

PRODUCT APPLICATIONS

- Secures material for use in indoor and outdoor applications and harsh weather environments.
- Great permanent bond holding power

FEATURES

- Smooth, easy release from hand rolls for easy application
- Ultra strong & durable



Peel Adhesion	15N/24mm
Static Shear (1000g)	10000 g +1440 min
Shear (180 degree)	64 lbs.
Tape Color	Clear / Opaque
Total Thickness	4.0 mil (102 micron)
Adhesive	Solvent Acrylic
Application Range	35°F to 95°F
Operating Range	20°F to 275°F
Sizes (Width)	3 mm to 1220 mm
Sizes (Length)	60 yards
Storage	40°F to 80°F 40% to 55% Humidity
Shelf Life	24 months
Applications	Indoor & Outdoor

NOMINAL VALUES

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



A Universal Company

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030

www.incrediseal.com | sales@incrediseal.com

Customer Service: (410) 825-8300