

**TECHNICAL SPECIFICATIONS**

DSPB-800.G

**DESCRIPTION**

Double sided permanent bond tape provides a long lasting secure bond when the highest adhesion levels are required.

The tape is commonly used to replace rivets and fasteners and can be used to secure a variety of materials like glass, plastic, metal, laminates, wood and even rock of concrete for specialty applications.

**PRODUCT APPLICATIONS**

- Secures material for use in indoor and outdoor applications and harsh weather environments.
- Great permanent bond holding power

**FEATURES**

- Smooth, easy release from hand rolls for easy application
- Ultra strong & durable



<b>Peel Adhesion</b>	30N/24mm
<b>Static Shear (1000g)</b>	10000 g +10000 min
<b>Shear (180 degree)</b>	110 lbs.
<b>Tape Color</b>	Gray
<b>Total Thickness</b>	800 mic (0.80 mm)
<b>Adhesive</b>	Acrylic
<b>Application Range</b>	35°F to 95°F
<b>Operating Range</b>	20°F to 275°F
<b>Sizes (Width)</b>	3 mm to 900 mm
<b>Sizes (Length)</b>	18 yards
<b>Storage</b>	40°F to 80°F 40% to 55% Humidity
<b>Shelf Life</b>	24 months
<b>Applications</b>	Indoor & Outdoor

**NOMINAL VALUES**

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



*A Universal Company*

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030  
www.IncrediSeal.com | sales@IncrediSeal.com

**Customer Service:** (888) 496-2747