

**DESCRIPTION**

Extremely high tack double sided Polyethylene Terephthalate (PET) with excellent shear stability, tensile force and water resistance.

Superior adhesion properties made from Synthetic Rubber and Resin, fast quick adhesion, high tensile strength, and easy unwind ensure consistent, reliable seals to a variety of materials including, corrugated, linerboard, plastics and metals.

**PRODUCT APPLICATION**

- Used to adhere nameplates and signage on walls and porous substrates
- Splicing tape application for the flexographic printing and paper industry
- Great shear strength and holding power

**FEATURES**

- Smooth, easy release from rolls and easy application to media
- Ultra strong & durable PET



**TECHNICAL SPECIFICATIONS**

**DS-5120C**

<b>Adhesion to Steel</b> (ASTM 3330)	95 oz/in (24 N/25 mm)
<b>Tensile (Machine)</b> (ASTM D3759)	45 lb / inch width (200 N/25 mm)
<b>Tensile (Cross)</b> (ASTM D3759)	N/A
<b>Elongation</b> (ASTM D3759)	42%
<b>Total Thickness</b>	8.50 mil
<b>Backing (BOPP)</b>	5.75 mil
<b>Liner</b>	2.75 mil
<b>Adhesive</b>	Synthetic Rubber & Resin
<b>Application Range</b>	23°F to 158°F
<b>Operating Range</b>	23°F to 158°F
<b>Colors</b>	Clear
<b>Sizes (Width)</b>	3 mm to 1040 mm
<b>Sizes (Length)</b>	60 to 250 yards
<b>Storage</b>	40°F to 80°F 40% to 55% Humidity
<b>Shelf Life</b>	24 months

**NOMINAL VALUES**

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



*A Universal Company*

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030  
www.incrediseal.com | sales@incrediseal.com

**Customer Service:** (410) 825-8300